

Model: ECO 150 TMP

| | Description | Notes |
|----------------------------|---|---|
| Basics | Weight | 490Kgs |
| | Max Timber Diameter | 150mm |
| | Throughput | 4.5 tonnes per hour |
| Engine | Tractor Mounted | 25 - 45 hp |
| | Clutch | Yes |
| Chipping | Power Feed Rollers | Spring Tensioned Twin |
| | Disc Processor/ Flywheel | Disc |
| | Disc Blade Cutters | 2 |
| | | 720-900 Hours expected life on clean material |
| | Flywheel Speed | 2400 RPM |
| | Main Drive Shaft Bearings | Oversized, Greaseable |
| | Infeed Chute Aperture (W X H) | 800mm x 700mm |
| | Infeed Throat Aperture (W x H) | 150mm x 150mm |
| | Sound Pressure LPA | 93 dB(A) |
| Sound Power LWA | 117 dB(A) | |
| Controls | Throttle Control | Manual Lever type |
| | No Stress | Yes |
| Safety | Safety Bars | EN 13525 Compliant |
| | | Floating to equalize pressure at all points |
| | | Built in sections to remove cost of replacement |
| Discharge | Discharge Chute | Rotation of 280° to safeguard the operator |
| | | Adjustable end cap to direct material |
| Dimensions: | Length Transport | 1060mm |
| | Width Transport | 1745mm |
| | Height Discharge Chute Up | 2220mm |
| | Dimensions can be reduced for LCL and FCL Ocean Freight, please ask for details. | |
| Optional Equipment: | Corporate Colour Choice | Standard RAL Colours only |